

TZS16-0.5-95

Telecentric s-series objectives are measuring optics for industrial use.

The complete series contains the families TZS8, TZS12, TZS16 and TZS24.

Every family has members for 1/3", 1/2" and 2/3" sensors.

All objectives are equipped with fixed iris and fixed focus. Mechanical interfaces are perfect for integration purposes.

Customized Adjustments:

Adjustments of iris, working distance etc. Are possible any time.

Attachments:

Mounting blocks, coaxial illumination heads, ring light as well as telecentric backlight for highest precision are available on inquiry.



TZS16-0.5-95				
Ø Image circle	1/3"	1/2"	2/3"	1"
Width object field(VIS)	9,8 mm	13,1 mm	-	-
Height object field(VIS)	7,3 mm	9,8 mm	-	-
Wavelength	VIS 484nm - 656nm			
Interface	C - Mount			
Notes	All object fields are tolerated with $\pm 5\%$. ∞ indicates the whole imaging length, i.e. The distance of the front lens to the object. AA indicates the working distance, i.e. the distance of the mechanics to the object. All values are object-sided!			

Spectral range	VIS
Ø object field 1/3"	12,2 mm
Ø object field 1/2"	16,2 mm
Ø object field 2/3"	-
Ø object field 1"	-
Working distance (AA $\pm 2\%$)	95,0 mm
Imaging length ∞	-
Back focus distance s	-
Linear magnification	1:2,0
MAG (B) ($\pm 5\%$)	0,49
Telecentricity	< 0,1 mrad
MTF @ 32 lp/mm	65%
Depth of focus @ 16 lp/mm	$\pm 3,3$ mm
Distortion max.	1,21%
Aperture object-side	0,0250

