

# TZS12-0.6-155

Telecentric S-series lenses are measuring optics for industrial use.

The complete series contains the families TZS8, TZS12, TZS16 and TZS24.

Every family has members for 1/3", 1/2" and 2/3" sensors.

All objectives are equipped with fixed iris and fixed focus. Mechanical interfaces are perfect for integration purposes.

Customized Adjustments:

Adjustments of iris, working distance etc. are possible any time.

Attachments:

Mounting blocks, coaxial illumination heads, ring light as well as telecentric backlight for highest precision are available on inquiry.



TZS12-0.6-155				
Ø Image circle	1/3"	1/2"	2/3"	1"
Width object field(Vis)	8,0 mm	8,0 mm	-	-
Height object field(Vis)	6,0 mm	10,7 mm	-	-
Wavelength	VIS 486nm - 656nm			
Interface	C-Mount			
Notes	<p><b>TZS12-0.6-155 only restricted suitable for 1/2".</b>                      All object fields are tolerated with <math>\pm 5\%</math>.                      OO' indicates the whole imaging length of the image field (typically CCD chip) to the object.                      s means the object-sided back focus length, i. e. the distance of the front lens to the object.</p>			

Spectral Range	VIS
Ø Object field 1/3"	10,0 mm
Ø Object field 1/2"	13,3 mm
Ø Object field 2/3"	-
Ø Object field 1"	-
Working distance (AA $\pm 2\%$ )	155,0 mm
Imaging length OO'	-
Back focus distance s	-
Linear magnification	1:1,7
MAG (B) ( $\pm 5\%$ )	0,60
Telecentricity	< 4,0 mrad
Distortion max.	0,70%

