

TZS24-0.43-95

Telecentric S-series lenses are measuring optics for industrial use.

The complete series contains the families TZS8, TZS12, TZS16 and TZS24.

Every family has members for 1/3", 1/2" and 2/3" sensors.

All objectives are equipped with fixed iris and fixed focus. Mechanical interfaces are perfect for integration purposes.

Customized Adjustments:

Adjustments of iris, working distance etc. are possible any time.

Attachments:

Mounting blocks, coaxial illumination heads, ring light as well as telecentric backlight for highest precision are available on inquiry.



TZS24-0.43-95				
Ø Image circle	1/3"	1/2"	2/3"	1"
Width object field(Vis)	11,2 mm	14,9 mm	-	-
Height object field(Vis)	8,4 mm	11,2 mm	-	-
Wavelength	VIS 486nm - 656nm			
Interface	C-Mount			
Notes	All object fields are tolerated with $\pm 5\%$. OO' indicates the whole imaging length of the image field (typically CCD chip) to the object. s means the object-sided back focus length, i. e. the distance of the front lens to the object.			

Spectral Range	VIS
Ø Object field 1/3"	14,0 mm
Ø Object field 1/2"	18,6 mm
Ø Object field 2/3"	-
Ø Object field 1"	-
Working distance (AA $\pm 2\%$)	95,0 mm
Imaging length OO'	-
Back focus distance s	-
Linear magnification	1:2,3
MAG (B) ($\pm 5\%$)	0,43
Telecentricity	< 1,0 mrad
Distortion max.	1,00%

